



Donaldson  
FILTRATION SOLUTIONS

## DATA SHEET

### Filter media

Sintered Polyethylene

### Sintered Polyethylene

<b>Appearance</b>	White
<b>Use</b>	Sintamatic sintered tubes
<b>Composition</b>	Sintered polyethylene composite material
<b>Area weight</b>	1.8 kg/m <sup>2</sup>
<b>Thickness</b>	3.5 mm
<b>Area weight</b>	1.8 kg/m <sup>2</sup>
<b>Air Permeability (DIN 53887)</b>	1.05 m <sup>3</sup> /m <sup>2</sup> /min@200Pa
<b>Surface finish</b>	PTFE membrane
<b>Surface electrical resistance (BGR 132)</b>	N/A
<b>IFA/BIA category (DIN 660335-2-69)</b>	Class M
<b>Temperature (dry heat)</b>	
Continuous	-20 to +70 °C
Peaks	up to 75 °C
<b>Chemical resistance</b>	
Hydrolysis	Excellent
Acids	Very good
Oxidising agents	Good
<b>Abrasion resistance</b>	Excellent
<b>Supports combustion</b>	Yes
<b>What to avoid</b>	Can be degraded by strong oxidising agents such as nitric acid, bromine or chlorine etc. Some organic solvents such as toluene may cause swelling. Avoid very cohesive, sticky materials or moisture sensitive dusts which are likely to crust on the media surface. Also avoid those materials containing oils, fats and greases, etc.
<b>Suitable applications</b>	Sintered elements are suitable for the vast majority of chemical conditions likely to be encountered in Sintamatic applications. Any dust handled should be dry and free flowing, free from any oils, fats or greases etc.